



DESCRIPTION

TERMINAL EQUIPMENT

Technical Field

5 The present invention relates to ~~a~~ terminal equipment (a terminal device) provided with a wireless interface, ~~which belongs to the International Patent Classification "H04N5/64"~~.

Background Art

10 Recently, the use of a wireless LAN (local area network) ~~is extending~~ has expanded rapidly thanks to its convenience of requiring no connection cable. Thus, as disclosed in, for example, Japanese Patent Laid-Open Publication No. 8-107369 (1996), the wireless LAN attracts
15 wide attention ~~as to~~ not only for its use ~~for~~ as a so-called TCP/IP (Transmission Control Protocol/Internet Protocol) ~~connection~~ connection, but its use as an audio and video transmission interface. Meanwhile, at present, the frequency used in the wireless LAN is shifting from a 2.4
20 GHz-band to a 5 GHz-band ~~enabling~~ which enables higher-capacity transmission.

 Hereinafter, ~~a~~ conventional terminal equipment provided with a wireless interface is described with reference to Figs. 5 and 6. Fig. 5 is a schematic
25 fragmentary side sectional view of the conventional

terminal equipment provided with the wireless interface and Fig. 6 is a fragmentary perspective view of a rear portion of the conventional terminal equipment of Fig. 5. In Figs. 5 and 6, the conventional terminal equipment includes a wireless module 10, a printed circuit board 4 and a housing 5 having a rear panel formed with a slot 9 for fitting the wireless module 10 thereinto. The wireless module 10 further includes a wireless module body 1, a communication means such as a built-in antenna 2 which is provided at one end portion of the wireless module body 1 so as to transmit and receive radio signals to and from a wireless network to be connected to the terminal equipment and a Personal Computer Memory Card International Association (PCMCIA) connector 3 which is provided at the other end portion of the wireless module body 1 so as to be connected to the terminal equipment when the wireless module 10 has been fitted into the slot 9 of the housing 5. As shown in Fig. 6, when the wireless module 10 has been fitted into the slot 9 of the rear panel of the housing 5, the built-in antenna 2 of the wireless module 10 is projected out of the slot 9 on a rear face of the housing 5.

~~Then,~~The operation of the conventional terminal equipment provided with the wireless interface, which has the above described arrangement, is now described. A modulated wave transmitted from the wireless network to be

connected to the terminal equipment is received by the built-in antenna 2 provided on the wireless module 10 and is converted into a baseband signal after its demodulation in the wireless module 10. Thereafter, via the PCMCIA
5 connector 3 provided on the printed circuit board 4 of the terminal equipment, the baseband signal is subjected to a processing based on a predetermined protocol by a signal processing circuit formed on the printed circuit board 4 of the terminal equipment and is converted into desired digital
10 data. At the time of transmission from the terminal equipment to the wireless network, the operation is performed in the reverse sequence of the ~~above-mentioned~~ above-mentioned one.

However, in the conventional terminal equipment
15 referred to above, since the wireless module 10 is fitted into the slot 9 of the rear panel of the housing 5 of the terminal equipment, transmission and reception radio waves are likely to be intercepted by the housing 5 ~~in case when~~ when the terminal equipment performs transmission and reception
20 with the wireless network. Meanwhile, the conventional terminal equipment has disadvantages in that since ~~raise of~~ the increase in gain of the built-in antenna 2 and the transmission power of the wireless module 10 ~~is~~ are limited by ~~such the~~ the physical and electrical restraints ~~as use of the~~
25 PCMCIA interface, it is difficult to secure communication

quality and extend a radio signal reach distance between the terminal equipment and the wireless network.

~~Disclosure~~ Summary of the Invention

5 The present invention has for its object to provide, with a view to eliminating the ~~above mentioned~~ above-mentioned drawbacks of the prior art, ~~a terminal equipment~~ (a terminal device) in which performance of a built-in antenna of a wireless module ~~can be~~ is raised easily.

10 In order to accomplish this object of the present invention, ~~a terminal equipment of the present invention is used by mounting~~ has mounted thereon a wireless module including a communication device having a transmission and reception antenna for connection to a wireless network.

15 The terminal equipment includes a first antenna unit which is connected to the transmission and reception antenna physically or spatially and a second antenna unit which is connected to the first antenna unit and transmits and receives radio signals directly to and from the wireless

20 network.

Brief Description of Drawings

Fig. 1 is a schematic fragmentary side sectional view of ~~a terminal equipment~~ according to a first embodiment of the present invention.

25 Fig. 2 is a cutaway fragmentary front elevational

view of the terminal equipment of Fig. 1.

Fig. 3 is a cutaway fragmentary perspective view of a front portion of the terminal equipment of Fig. 1.

Fig. 4 is a block diagram showing an antenna device employed in—a terminal equipment which is a modification of the terminal equipment of Fig. 1.

Fig. 5 is a schematic fragmentary side sectional view of—a prior art terminal equipment provided with a wireless interface.

Fig. 6 is a fragmentary perspective view of a rear portion of the prior art terminal equipment of Fig. 5.

Best Mode for Carrying Out the Invention

Hereinafter, one embodiment of the present invention is described with reference to the drawings.

(~~First embodiment~~ Embodiment)

Fig. 1 is a schematic fragmentary side sectional view of—a terminal equipment (a terminal device) according to a first embodiment of the present invention, Fig. 2 is a cutaway fragmentary front elevational view of the terminal equipment of Fig. 1 and Fig. 3 is a cutaway fragmentary perspective view of a front portion of the terminal equipment of Fig. 1.

In Figs. 1 to 3, in the same manner as a conventional terminal equipment, this terminal equipment includes a wireless module 10, a printed circuit board 4 and

a housing 5 formed with a slot 9 for fitting the wireless module 10 thereinto. The card type wireless module 10 having an interface function includes a wireless module body 1, a communication means such as a built-in antenna 2 which is provided at one end portion of the wireless module body 1 so as to transmit and receive radio signals to and from a wireless network to be connected to the terminal equipment and a PCMCIA connector 3 which is provided at the other end portion of the wireless module body 1 so as to be connected to the terminal equipment when the wireless module 10 has been fitted into the slot 9 of the housing 5.

In contrast with the conventional terminal equipment of Figs. 5 and 6 in which the slot 9 is formed on a rear panel of the housing 5, the slot 9 is formed on a front panel of the housing 5 in the terminal equipment of the present invention. Thus, as shown in Figs. 1 and 3, when the wireless module 10 has been fitted into the slot 9 of the front panel of the housing 5, the built-in antenna 2 of the wireless module 10 is projected out of the slot 9 on the front panel of the housing 5. Furthermore, in contrast with the conventional terminal equipment of Figs. 5 and 6, the terminal equipment of the present invention includes an antenna device 20 composed of first and second antenna units 13 and 14, and a cover 15 for accommodating the

built-in antenna 2 of the wireless module 10 fitted into the slot 9 and the antenna device 20, which is attached to the front panel of the housing 5. The first antenna unit 13 is connected to the built-in antenna 2 physically or spatially so as to perform transmission and reception with the built-in antenna 2, while the second antenna unit 14 is connected to the first antenna unit 13 so as to transmit and receive radio signals directly to and from the wireless network to be connected to the terminal equipment.

10 ~~Then,~~The operation of the terminal equipment of the above described arrangement is now described. A modulated wave transmitted from the wireless network to be connected to the terminal equipment is initially received by the second antenna unit 14 in the cover 15 attached to the front panel of the housing 5 of the terminal equipment and is guided to the first antenna unit 13. Since the first antenna unit 13 is electromagnetically coupled to the built-in antenna 2 of the wireless module 10 fitted into the slot 9, the modulated wave is delivered into the wireless module 10 so as to be converted into a baseband signal. Thereafter, via the PCMCIA connector 3 provided on the printed circuit board 4 of the terminal equipment, the baseband signal is subjected to a processing based on a predetermined protocol by a signal processing circuit formed on the printed circuit board 4 of the terminal

15
20
25

equipment and is converted into desired digital data. At the time of transmission from the terminal equipment to the wireless network, the operation is performed in ~~the reverse sequence of the above-mentioned one~~ above-mentioned
5 sequence.

As described above, since the first antenna unit 13 for performing transmission and reception with the built-in antenna 2 of the wireless module 10 and the second antenna unit 14 for performing transmission and reception
10 with the wireless network to be connected to the terminal equipment are disposed at a location where radio waves are least likely to be intercepted, for example, the front panel of the housing 5 of the terminal equipment, communication quality can be upgraded easily.

15 Meanwhile, in this embodiment, the PCMCIA connector 3 is used as an interface of the wireless module ~~10_10~~, but it is needless to say that the same effects can be gained even if other ~~interfaces~~ interfaces, such as a Secure Digital (SD) card and a Memory ~~Stick~~ Stick, are
20 used. Furthermore, elements of various types and shapes such as a dielectric, a slot and a patch can be used as the first and second antenna units 13 and 14 and the degree of freedom in design of dimensions and layout of the first and second antenna units 13 and 14 is quite high.

25 In Fig. 4 showing an antenna device 20' of ~~a~~

terminal equipment which is a modification of the terminal equipment of Fig. 1, a high-frequency amplifier circuit 16 having a gain of 1 or more is inserted between the first and second antenna units 13 and 14.

5 Meanwhile, the first and second antenna units 13 and 14 may also be fixed to an openable cover.

As is clear from the foregoing description of the present invention, since the first antenna unit for performing transmission and reception with the built-in antenna of the wireless module and the second antenna unit for performing transmission and reception with the wireless network to be connected to the terminal equipment are disposed at the location where radio waves are least likely to be intercepted, for example, the front panel of the housing of the terminal equipment, it is possible to upgrade communication quality and extend a radio signal reach distance between the terminal equipment and the wireless network. In addition, it is possible to easily upgrade such properties as directivity and gain in the first and second antenna units provided at the location which is comparatively free from physical or electrical restrictions, for example, the front panel of the housing of the terminal equipment.

10
15
20

Meanwhile, in the present invention, if the high-frequency amplifier circuit is inserted between the first and

25

second antenna units, transmission power and a carrier-to-noise ratio (C/N) for reception are improved, so that communication quality can be further upgraded.

ABSTRACT

A ~~terminal~~Terminal equipment ~~is used by~~
~~mounting~~has mounted thereon a wireless module including
a communication device having a transmission and
5 reception antenna for connection to a wireless network and
includes a first antenna unit which is connected to the
transmission and reception antenna physically or spatially
and a second antenna unit which is connected to the first
antenna unit and transmits and receives radio signals
10 directly to and from the wireless network such that not only
communication quality is ~~upgraded~~upgraded, but a radio
signal reach distance between the terminal equipment and
the wireless network is extended.